



AS SAFE SECURITY SERVICES PTY LTD

Fact 2, 8 Freeman St, Campbellfield, Vic, 3061.
 PO Box 422, Wallan, Vic, 3756.

Tel: (03) 9465 7055
 Fax: (03) 9357 7212



AUSTRAL FLOOR SAFES

EXPLOSIVE, DRILL AND FORCE RESISTING (EDF) INGROUND FLOOR SAFES

STANDARD FEATURES

DOOR: Heavy cast high-tensile steel construction fully chromium plated. Door section is secured below 25mm thick steel top plate. Special hinge is to move heavy door only and is not part of security.

LOCKING: 1 million change combination lock mounted on hardened steel, drill resistant plate.

Two spring loaded reloading devices incorporated in door and lock.

BODY: Heavy gauge steel with 25mm thick steel top plate machined to accept door with minimum of tolerance.

HINGES: Hinged door for ease of operation. (Doors are interchangeable).

LID: Heavy steel lid (not shown), fits flush with top of safe.

Deposit chute may be fitted if required.



INSTALLATION \$

MODEL A14

MODEL	CODE	HEIGHT	WIDTH	DEPTH	WEIGHT	PRICE
A14	External	440mm	360mm	360mm	36kg	\$
	Internal	330mm	305mm	305mm		
A9	External	305mm	360mm	360mm	32kg	\$
	Internal	230mm	305mm	305mm		

SUGGESTED INSURABLE CASH RATING FOR AUSTRAL FLOOR SAFES IS AN UNSUPPORTED (NO ALARMS) SITUATION IS \$20,000