

AS SAFE SECURITY SERVICES PTY LTD

Fact 2, 8 Freeman St, Campbellfield, Vic, 3061.
 PO Box 422, Wallan, Vic, 3756.

Tel: (03) 9357 0112
 Fax: (03) 9357 7212

GUARDALL IN FLOOR SAFES



MODEL GUAD
 FITTED WITH A LAGARD 33E 6 DIGIT
 TOUCH PAD POWERED BY ONE 9V
 ALKALINE BATTERY.

MODEL GUAC
 FITTED WITH S & G 3 WHEEL
 1 MILLION CHANGE
 COMBINATION


MODEL GUAK
 FITTED WITH A
 SIX LEVER PICK
 RESISTANT
 KEY LOCK

- SPRING ASSISTED DOOR PIVOT
- REMOVABLE DOORS INTERCHANGE
- HARD PLATE TO PROTECT LOCK AREA
- EMERGENCY RELOCKING DEVICE

	EXTERNAL		INTERNAL		WEIGHT
HEIGHT	390		260		
BASE	350	375	270	295	
	DEPTH	WIDTH	DEPTH	WIDTH	
PRICE	\$	\$	\$		
MODEL	GUAD	GUAC	GUAK		
INSTALLATION	\$				

MADE IN AUSTRALIA

**SUGGESTED INSURABLE CASH RATING FOR GUARDALL FLOOR SAFES
 IN AN UNSUPPORTED (NO ALARMS) DOMESTIC SITUATION IS \$10,000.**



AS SAFE SECURITY SERVICES PTY LTD

Fact 2, 8 Freeman St, Campbellfield, Vic, 3061.
PO Box 422, Wallan, Vic, 3756.

Tel: (03) 9357 0112
Fax: (03) 9357 7212

GUARDALL IN FLOOR SAFES

RECOMMENDED INSTALLATION PROCEDURE

The safes may be installed in either concrete or timber floors. The opening in the floor should be at least 500mm square by 500mm deep.

The safe should be secured with a strong mix concrete 1 x sand, 1 x stone, 1 x cement. Steel reinforcing material can also be used to help bond the concrete and provide better security.

It is recommended that the mix be poured so that a concrete cover of at least 100mm (4") exists around each side of the safe and brought level with top.

Floor safes are not waterproof. In damp situation the concrete should contain a waterproofing agent such as "Silasec" or "Yurite" (available from hardware stores). Whilst the concrete is setting, the door should be removed.

**INTERCHANGEABLE
DOOR REMOVES TO
FACILITATE SERVICE
& INSTALLATION.**



**FLUSH FITTING LID TO AID
CONCEALMENT AND FIRE
PROTECTION.**

MADE IN AUSTRALIA

**SUGGESTED INSURABLE CASH RATING FOR GUARDALL FLOOR SAFES
IN AN UNSUPPORTED (NO ALARMS) DOMESTIC SITUATION IS \$10,000.**

Email: info@esafes.com.au
Web: www.esafes.com.au