

AS SAFE SECURITY SERVICES PTY LTD

Fact 2, 8 Freeman St, Campbellfield, Vic, 3061.
PO Box 422, Wallan, Vic, 3756.


Tel: (03) 9357 0112
Fax: (03) 9357 7212

LORD
SAFE C°

Data Safes

home office retail medical cash management record protection firearms




Email: info@esafes.com.au
Web: www.esafes.com.au



AS SAFE SECURITY SERVICES PTY LTD

Fact 2, 8 Freeman St, Campbellfield, Vic, 3061.
PO Box 422, Wallan, Vic, 3756.

Tel: (03) 9357 0112
Fax: (03) 9357 7212

Data Safe

MODEL	EXTERNAL DIMENSIONS(mm)			INTERNAL DIMENSIONS(mm)			CAPACITY LITRES	MASS Kg	FIRE RATING HOURS	SHELVES	QUANTITY STORAGE <small>CPA & S.S. Supply</small>
	HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH					
125D	420	352	433	213	153	172	5.8	50	1	1	23 / 132
530D	522	404	440	303	193	172	10.2	68	1	1	42 / 262
070D	695	500	500	408	273	202	22.6	113	1.5	2	87 / 612
080D	876	520	520	569	273	202	31.4	157	1.5	3	116 / 828
825D	830	690	720	483	403	382	76.2	267	1.5	3	240 / 2288
DT4	1043	770	874	693	514	505	180	350	1	-	Contact
DT5	1495	834	921	1100	514	500	283	560	2	-	Sales
DT6	1485	1290	851	1100	974	425	455	770	2	-	Representative

BODY -
Steel lining enclosing a barrier of Styronite fire resistant material.

DOOR -
Pressed steel construction enclosing a barrier of Styronite fire resistant material. The door opens 180° on hinge assemblies that facilitate easy removal of the door for delivery or replacement. The inner cabinet has an insulated door with a heat, dust and moisture resistant gasket and is secured by a pressure clenching mechanism that provides an airtight seal.

BOLTWORK -
The door is secured to the body by moving bolts at the top, bottom and opening side and also by fixed bolts on the hinge side. When the door is open the moving bolts remain retracted and automatically lock when the door is closed. Automatic bolt action prevents damage to the boltwork and cabinet, and enables speedy locking in case of emergency.

LOCKING -
The door is secured by a 4 pin tumbler keylock. The DT Series is fitted with a high security double bit key lock.

INTERNAL FITTINGS -
Models 125D to 825D are supplied with removable shelves, refer to the table for quantities. Adjustable slide out shelves are available for the DT Series safes.

FINISH -
Leathertone painted finish (as depicted).

FIRE TESTS -
Fire Resistant and Impact tested and certified.

Models 125D to 825D -
KSG4500, P-S1TS & P-S2TS - Korean Standards Association (KSA).
NT Fire 017 - Swedish National Testing & Research Institute (SP).
Class 350 - Underwriters Laboratories Inc. U.S.A. (UL).

Models DT4 to DT6
JIS One /Two Hour Combined Fire and Impact Test - Japan Industrial Standard

In line with our policy to provide the best in security, we reserve the right to incorporate any improvements or alter any part of the specification without prior notice.

Distributed by: